

Contents

1 Introduction	1
1.1 Goals	2
1.2 Dissertation Organization	3
2 State of the Art	5
2.1 Background Concepts	5
2.1.1 What is an Embedded Linux System?	5
2.1.2 Boot Sequence	7
2.1.2.1 Hardware Initialization	7
2.1.2.2 Boot loader	8
2.1.2.3 Linux kernel	9
2.1.2.4 User Space	11
2.2 Measurement Process	12
2.2.1 Boot time interval	13
2.2.2 Measurement Techniques	13
2.2.2.1 Serial Log Listening	13
2.2.2.2 GPIO toggling	15
2.3 Optimization Techniques	15
2.3.1 Compilation Options	15
2.3.1.1 Static and Dynamic Compilation	16
2.3.1.2 Compilation Flags	17
2.3.2 User-Space Optimization	18
2.3.2.1 Tools to reorder systemd services hierarchy	18
2.3.2.2 Simplifying SysVinit scripts	20
2.3.2.3 Pre-Init	20
2.3.3 Filesystem Optimization	21
2.3.4 Kernel Optimization	21
2.3.5 Linux Suspension	22
2.3.6 Boot Loader optimization	23
2.3.6.1 Configuration options optimization	23
2.3.6.2 Reducing Boot loader script	24
2.3.6.3 Falcon Mode	24
2.3.7 Memory Selection	25
2.3.7.1 SD card	25
2.3.7.2 Flash memory	26

2.4	Related Work	27
2.4.1	Boot time approach methodology	27
2.4.2	GUI application solution	29
2.4.3	Extreme minimalistic solution	30
2.4.4	Similar platform solution	31
3	Case-study Specifications	33
3.1	System Description	33
3.1.1	P689 overall architecture	33
3.1.2	HUD initialization sequence	34
3.2	Development Environment	35
3.2.1	Target Description	36
3.2.2	Host Description	36
3.2.2.1	Yocto Project	37
3.2.2.2	Layers of Yocto Project	38
3.2.2.3	Yocto Project's Licensing	39
4	Implementation	41
4.1	Measurement preparation	41
4.1.1	Boot time measurement	41
4.1.2	Changes on HUD application	43
4.2	Optimization Techniques	43
4.2.1	HUD Compilation	43
4.2.2	File system optimization	45
4.2.3	Pre-Init	46
4.2.4	Kernel Optimization	47
4.2.5	Falcon mode	50
4.2.6	Memory Selection	52
4.2.7	Final boot sequence	52
4.2.8	Additional Work	53
4.2.8.1	systemd's Units Analysis	54
4.2.8.2	U-Boot's boot script reduction	56
4.2.8.3	Automating Yocto's build process	56
5	Results	59
5.1	Compilation Comparison	59
5.2	File system reduction	61
5.3	Service and Pre-Init	62
5.4	Kernel configuration	63
5.5	Memory comparison	64
5.6	Falcon Mode	65
6	Conclusion	67
6.1	Results Discussion	67
6.2	Future Work	70

I	U-Boot's Boot Command Flowchart	73
II	Peripheral layout of the i.MX6Q Sabresd Board	75
III	Overall architecture of P689	77
IV	Qt libraries configuration	79
V	List of used dynamic libraries	81
VI	Modified flowchart of HUD application	83
	References	85